

**Amendment to the Claims:**

This listing of claims will replace all prior versions, and listings of claims in the application:

**Listing of Claims:**

- 1                   1.       (Currently amended): A method comprising:  
2                   identifying an address portion of a first message in an address slice of a switch,  
3                   the first message associated with a first priority, the address portion of the first message  
4                   including a first routing portion specifying a network resource;  
5                   identifying an address portion of a second message in the address slice, the second  
6                   message associated with a second priority, the address portion of the second message including a  
7                   second routing portion specifying the same network resource;  
8                   identifying a non-address portion of the first message in a non-address slice of the  
9                   switch;  
10                  identifying a non-address portion of the second message in the non-address slice,  
11                  wherein neither of the non-address portions includes a routing portion specifying the network  
12                  resource;  
13                  selecting, independently in each slice, the same one of either the first message or  
14                  the and second messages as a selected message, based on the first and second priorities;  
15                  transferring the address portion of the selected message to the network resource  
16                  specified by the routing portion of the address portion of the selected message;  
17                  sending the routing portion of the address portion of the selected message from  
18                  the address slice to the non-address slice; and  
19                  transferring the non-address portion of the selected message to the network  
20                  resource specified by the routing portion of the address portion of the selected message.
- 1                   2.       (Original): The method of claim 1, further comprising: associating the  
2                   first and second priorities with the first and second messages based on the ages of the first and  
3                   second messages.

1           3.       (Original): The method of claim 1, further comprising:  
2           dividing each message to create the address portions and non-address portions;  
3           sending the address portions to the address slice; and  
4           sending the non-address portions to the non-address slice.

1           4.       (Original): The method of claim 1, wherein the network resource is a  
2 memory resource.

1           5.       (Original): The method of claim 1, further comprising:  
2           sending the selected address portion to a further address slice;  
3           and sending the selected non-address portion to a further non-address slice.

1           6.       (Original): The method of claim 1, wherein the network resource is a  
2 processor.

1           7.       (Original): The method of claim 1, wherein the network resource is a  
2 crossbar.

1           8.       (Currently amended): A method for use in an address slice of a switch  
2 having the address slice and a non-address slice, comprising:  
3           identifying an address portion of a first message, the first message associated with  
4 a first priority, the address portion of the first message including a first routing portion specifying  
5 a network resource, wherein a non-address portion of the first message resides in a non-address  
6 slice of the switch;  
7           identifying an address portion of a second message, the second message  
8 associated with a second priority, the address portion of the second message including a second  
9 routing portion specifying the same network resource, wherein a non-address portion of the  
10 second message resides in the non-address slice, wherein neither of the non-address portions  
11 includes a routing portion specifying the network resource;

12                    in a first of the two slices, selecting one of a selected message from either the first  
13 message or the and-second messages based on the first and second priorities, wherein the  
14 selected message is also selected by the second of the two slices independently of the first of the  
15 two slices; selects the same one of the first and second messages based on the first and second  
16 priorities; and

17                    transferring the address portion of the selected message to the network resource  
18 specified by the routing portion of the address portion of the selected message; and

19                    sending the first and second routing portions from the address slice to the non-  
20 address slice, wherein the non-address slice sends the non-address portion of the selected  
21 message to the network resource specified by the routing portion of the address portion of the  
22 selected message.

1                    9.        (Currently amended): A method for use in a non-address slice of a switch  
2 having the non-address slice and an address slice, comprising:

3                    identifying a non-address portion of a first message, the first message associated  
4 with a first priority, wherein an address portion of the first message resides in an address slice of  
5 the switch, the address portion of the first message including a first routing portion specifying a  
6 network resource;

7                    identifying a non-address portion of a second message, the second message  
8 associated with a second priority, wherein an address portion of the second message resides in  
9 the address slice, the address portion of the second message including a second routing portion  
10 specifying the same network resource, wherein neither of the non-address portions includes a  
11 routing portion specifying the network resource;

12                    in the address slice, selecting as a selected message one of the first and second two  
13 messages based on the first and second priorities, wherein the second non-address slice  
14 independently selects the same selected message from the two messages one of the first and  
15 second messages based on the first and second priorities; and

16                    receiving the first and second routing portions from the address slice; and

transferring the non-address portion of the selected message to the network resource specified by the routing portion of the address portion of the selected message; and wherein the address slice sends the address portion of the selected message to the network resource specified by the routing portion of the address portion of the selected message.

10. (Currently amended): A method comprising:  
identifying a first portion of a first message in a first slice of a switch, the first message associated with a first priority, the first portion of the first message including a first routing portion;  
identifying a second portion of the first message in a second slice of the switch, the second portion of the first message including a second routing portion, the first and second routing portions together specifying a network resource;  
identifying a first portion of a second message in the first slice, the second message associated with a second priority, the first portion of the second message including a third routing portion;  
identifying a second portion of the second message in the second slice, the second portion of the second message including a fourth routing portion, the third and fourth routing portions together specifying the network resource;  
selecting, independently in each slice, the same selected message as between one of the first and second messages based on the first and second priorities;  
transferring the one of the first and third routing portions corresponding to the selected message from the first slice to the second slice;  
sending the second portion of the selected message from the second slice to the network resource specified by the combination of the one of the first and third routing portions corresponding to the selected message and the one of the second and fourth routing portions corresponding to the selected message;  
transferring the one of the second and fourth routing portions corresponding to the selected message from the second slice to the first slice; and

24                    sending the first portion of the selected message from the first slice to the network  
25 resource specified by the combination of the one of the first and third routing portions  
26 corresponding to the selected message and the one of the second and fourth routing portions  
27 corresponding to the selected message.

1                    11.    (Original): The method of claim 10, further comprising:  
2                    associating the first and second priorities with the first and second messages based  
3 on the ages of the first and second messages.

1                    12.    (Original): The method of claim 10, further comprising:  
2                    dividing each message to create the first and second portions;  
3                    sending the first portions to the first slice; and  
4                    sending the second portions to the second slice.

1                    13.    (Original): The method of claim 10, wherein the network resource is a  
2 memory resource.

1                    14.    (Original): The method of claim 10, wherein the network resource is a  
2 processor.

1                    15.    (Original): The method of claim 10, wherein the network resource is a  
2 crossbar.

1                    16.    (Currently amended): A method for use in a first slice of a switch having  
2 first and second slices, comprising:  
3                    identifying a first portion of a first message in the first slice, the first message  
4 associated with a first priority, the first portion of the first message including a first routing  
5 portion, wherein a second portion of the first message resides in the second slice of the switch,  
6 the second portion of the first message including a second routing portion, the first and second  
7 routing portions together specifying a network resource;

8 identifying a first portion of a second message in the first slice, the second  
9 message associated with a second priority, the first portion of the second message including a  
10 third routing portion, wherein a second portion of the second message resides in the second slice,  
11 the second portion of the second message including a fourth routing portion, the third and fourth  
12 routing portions together specifying the network resource;

13 selecting ~~one of either~~ the first ~~and or the~~ second messages based on the first and  
14 second priorities as a selected message, wherein ~~the second~~ each slice performs the selecting  
15 independently of the other and selects the same selected message is selected by each slice~~one of~~  
16 ~~the first and second messages based on the first and second priorities;~~

17 receiving the one of the second and fourth routing portions corresponding to the  
18 selected message from the second slice;

19 sending the first portion of the selected message to the network resource specified  
20 by the combination of the one of the first and third routing portions corresponding to the selected  
21 message and the one of the second and fourth routing portions corresponding to the selected  
22 message; and

23 transferring the one of the first and third routing portions corresponding to the  
24 selected message to the second slice; and wherein

25 the second slice sends the second portion of the selected message to the network  
26 resource specified by the combination of the one of the first and third routing portions  
27 corresponding to the selected message and the one of the second and fourth routing portions  
28 corresponding to the selected message.

1 17. (Currently amended): An apparatus comprising:  
2 means for identifying an address portion of a first message in an address slice of a  
3 switch, the first message associated with a first priority, the address portion of the first message  
4 including a first routing portion specifying a network resource;  
5 means for identifying an address portion of a second message in the address slice,  
6 the second message associated with a second priority, the address portion of the second message  
7 including a second routing portion specifying the same network resource;

8 means for identifying a non-address portion of the first message in a non-address  
9 slice of the switch;

10 means for identifying a non-address portion of the second message in the non-  
11 address slice, wherein neither of the non-address portions includes a routing portion specifying  
12 the network resource;

13 means for selecting, independently in each slice, the same selected message as  
14 between one of the first and second messages based on the first and second priorities;

15 means for transferring the address portion of the selected message to the network  
16 resource specified by the routing portion of the address portion of the selected message;

17 means for sending the routing portion of the address portion of the selected  
18 message from the address slice to the non-address slice; and

19 means for transferring the non-address portion of the selected message to the  
20 network resource specified by the routing portion of the address portion of the selected message.

1 18. (Original): The apparatus of claim 17, further comprising:

2 means for associating the first and second priorities with the first and second  
3 messages based on the ages of the first and second messages.

1 19. (Original): The apparatus of claim 17, further comprising:

2 means for dividing each message to create the address portions and non-address  
3 portions;

4 means for sending the address portions to the address slice; and

5 sending the non-address portions to the non-address slice.

1 20. (Original): The apparatus of claim 17, wherein the network resource is a  
2 memory resource.

1 21. (Original): The apparatus of claim 17, further comprising:

2 means for sending the selected address portion to a further address slice; and

3 means for sending the selected non-address portion to a further non-address slice.

22. (Original): The apparatus of claim 17, wherein the network resource is a processor.

23. (Original): The apparatus of claim 17, wherein the network resource is a crossbar.

24. (Currently amended): An apparatus for use in an address slice of a switch having the address slice and a non-address slice, comprising:

means for identifying an address portion of a first message, the first message associated with a first priority, the address portion of the first message including a first routing portion specifying a network resource, wherein a non-address portion of the first message resides in a non-address slice of the switch;

means for identifying an address portion of a second message, the second message associated with a second priority, the address portion of the second message including a second routing portion specifying the same network resource, wherein a non-address portion, of the second message resides in the non-address slice, wherein neither of the non-address portions includes a routing portion specifying the network resource;

means for selecting one of the first ~~and or~~ second messages, as a selected message, based on the first and second priorities, wherein ~~the second each slice performs the selecting independently of the other slice and selects the same selected message; one of the first and second messages based on the first and second priorities; and~~

means for transferring the address portion of the selected message to the network resource specified by the routing portion of the address portion of the selected message; and

means for sending the first and second routing portions from the address slice to the non-address slice, wherein the non-address slice sends the non-address portion of the selected message to the network resource specified by the routing portion of the address portion of the selected message.



1                   25.     (Currently amended): An apparatus for use in a non-address slice of a  
2 switch having the non-address slice and an address slice, comprising:  
3                   means for identifying a non-address portion of a first message, the first message  
4 associated with a first priority, wherein an address portion of the first message resides in an  
5 address slice of the switch, the address portion of the first message including a first routing  
6 portion specifying a network resource;  
7                   means for identifying a non-address portion of a second message, the second  
8 message associated with a second priority, wherein an address portion of the second message  
9 resides in the address slice, the address portion of the second message including a second routing  
10 portion specifying the same network resource, wherein neither of the non-address portions  
11 includes a routing portion specifying the network resource;  
12                   means for selecting ~~one of~~ as a selected message the first ~~and or~~ second messages  
13 based on the first and second priorities, wherein ~~the second~~ each slice independently selects the  
14 same selected message; ~~one of the first and second messages based on the first and second~~  
15 ~~priorities; and~~  
16                   means for receiving the first and second routing portions from the address slice;  
17 and  
18                   means for transferring the non-address portion of the selected message to the  
19 network resource specified by the routing portion of the address portion of the selected message;  
20 and wherein  
21                   the address slice sends the address portion of the selected message to the network  
22 resource specified by the routing portion of the address portion of the selected message.

1                   26.     (Currently amended): An apparatus comprising:  
2                   means for identifying a first portion of a first message in a first slice of a switch,  
3 the first message associated with a first priority, the first portion of the first message including a  
4 first routing portion;  
5                   means for identifying a second portion of the first message in a second slice of the  
6 switch, the second portion of the first message including a second routing portion, the first and  
7 second routing portions together specifying a network resource;  
8                   means for identifying a first portion of a second message in the first slice, the  
9 second message associated with a second priority, the first portion of the second message  
10 including a third routing portion;  
11                  means for identifying a second portion of the second message in the second slice,  
12 the second portion of the second message including a fourth routing portion, the third and fourth  
13 routing portions together specifying the network resource;  
14                  means for selecting, independently in each slice, the same ~~one of~~ selected message  
15 from among the first and second messages based on the first and second priorities;  
16                  means for transferring the one of the first and third routing portions corresponding  
17 to the selected message from the first slice to the second slice;  
18                  means for sending the second portion of the selected message from the second  
19 slice to the network resource specified by the combination of the one of the first and third routing  
20 portions corresponding to the selected message and the one of the second and fourth routing  
21 portions corresponding to the selected message;  
22                  means for transferring the one of the second and fourth routing portions  
23 corresponding to the selected message from the second slice to the first slice; and  
24                  means for sending the first portion of the selected message from the first slice to  
25 the network resource specified by the combination of the one of the first and third routing  
26 portions corresponding to the selected message and the one of the second and fourth routing  
27 portions corresponding to the selected message.

1                   27.     (Original): The apparatus of claim 26, further comprising:  
2                   means for associating the first and second priorities with the first and second  
3 messages based on the ages of the first and second messages.

1                   28.     (Original): The apparatus of claim 26, further comprising:  
2                   means for dividing each message to create the first and second portions;  
3                   means for sending the first portions to the first slice; and  
4                   means for sending the second portions to the second slice.

1                   29.     (Original): The apparatus of claim 26, wherein the network resource is a  
2 memory resource.

1                   30.     (Original): The apparatus of claim 26, wherein the network resource is a  
2 processor.

1                   31.     (Original): The apparatus of claim 26, wherein the network resource is a  
2 crossbar.

1                   32.     (Currently amended): An apparatus for use in a first slice of a switch  
2 having first and second slices, comprising:  
3                   means for identifying a first portion of a first message in the first slice, the first  
4 message associated with a first priority, the first portion of the first message including a first  
5 routing portion, wherein a second portion of the first message resides in the second slice of the  
6 switch, the second portion of the first message including a second routing portion, the first and  
7 second routing portions together specifying a network resource;  
8                   means for identifying a first portion of a second message in the first slice, the  
9 second message associated with a second priority, the first portion of the second message  
10 including a third routing portion, wherein a second portion of the second message resides in the  
11 second slice, the second portion of the second message including a fourth routing portion, the  
12 third and fourth routing portions together specifying the network resource;

13                    means for selecting ~~one of a~~ selected message from among the first and second  
14 messages based on the first and second priorities, wherein the same selected message is selected  
15 in each second slice independently of the other slices~~selects the same one of the first and second~~  
16 ~~messages based on the first and second priorities;~~

17                    means for receiving the one of the second and fourth routing portions  
18 corresponding to the selected message from the second slice;

19                    means for sending the first portion of the selected message to the network  
20 resource specified by the combination of the one of the first and third routing portions  
21 corresponding to the selected message and the one of the second and fourth routing portions  
22 corresponding to the selected message; and

23                    means for transferring the one of the first and third routing portions corresponding  
24 to the selected message to the second slice; and wherein

25                    the second slice sends the second portion of the selected message to the network  
26 resource specified by the combination of the one of the first and third routing portions  
27 corresponding to the selected message and the one of the second and fourth routing portions  
28 corresponding to the selected message.